Fuji Power MOSFET SuperFAP-G series Target Specification ***PRELIMINARY***

2SK3530-01MR (800V/1.9Ω/7A)

1) Package

TO-220F

2) Absolute Maximum Ratings (Tc=25℃ unless otherwise specified)

Items	Symbols	Ratings	Units	
Drain-Source Voltage	V_{DS}	800	V	
Continuous Drain Current	I_D	±7	A	
Pulsed Drain Current	$I_{D(pulse)}$	±28	A	
Gate-Source Voltage	V_{GS}	±30	V	
Repetitive and Non-Repetitive Maximum Avalanche Current	I_{AR}	7	A	
Non-Repetitive Maximum Avalanche Energy	E_{AS}	235.3	mJ	*1
Maximum Drain-Source dV/dt	dV_{DS}/dt	20	kV/us	
Peak Diode recovery dV/dt	dV/dt	5	kV/us	*2
Maximum Power Dissipation	$P_{D\ @Tc=25℃}$	70	W	
	$P_{D\ @Ta=25℃}$	2.16	W	
Operating and Storage Temperature range	T_{ch}	150	℃	
	T_{stg}	-55 ～ +150	℃	

3)Electrical Characteristics (Tch=25℃ unless otherwise specified)

Items	Symbols	Test Conditions		min.	typ.	max.	Units
Drain-Source Breakdown Voltage	BV_{DSS}	I_D=250uA	V_{GS}=0V	800	---	---	V
Gate Threshold Voltage	V_{GS}(th)	I_D=250uA	V_{DS}=V_{GS}	3.0	---	5.0	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=800V	T_{ch}=25℃	---	---	50	μA
		V_{GS}=0V	T_{ch}=125℃	---	---	500	μA
Gate-Source Leakage Current	I_{GSS}	V_{GS}=±30V	V_{DS}=0V	---	---	100	nA
Drain-Source On-State Resistance	R_{DS}(on)	I_D=3.5A	VGS=10V	---	---	1.9	Ω
Input Capacitance	C_{iss}	V_{DS}=25V		---	830	---	pF
Output Capacitance	C_{oss}	V_{GS}=0V		---	100	---	
Reverse Transfer Capacitance	C_{rss}	f=1MHz		---	5	---	
Total Gate Charge	Qg	Vcc=400V		---	25	---	nC
Gate to Source Charge	Qgs	I_D=7A		---	7.5	---	
Gate to Drain (Miller) Charge	Qgd	V_{GS}=10V		---	7	---	
Avalanche Capability	I_{AV}	L=8.80mH	Tch=25℃	7	---	---	A
Diode Forward On-Voltage	V_{SD}	I_F=7A,VGS=0V,Tch=25℃		---	1.0	1.5	V

4) Thermal Characteristics

Items	Symbols	Test Conditions	min.	typ.	max.	Units
Channel to Case	Rth(ch-c)				1.79	℃/W
Channel to Ambient	Rth(ch-a)				58.0	℃/W

*1 L=8.80mH,Vcc=80V

***2 $I_F \leq -I_D$,-di/dt=50A/μs,Vcc≤BV_{DSS},Tch≤150°C**

This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.

a:Absolute max ratings were revised.

REVISIONS		DATE	NAME	APPROVED
	DRAWN	Sep.-09-'02	T. Kuboyama	
	CHECKED	Sep.-09-'02	T. Yamada	T. HOSEN

Fuji Electric Co.,Ltd.

DWG.NO. **MT5F12296 1/1** a

MA4LE